

REMS Power-Press ACC

Electro-hydraulic radial press 32 kN  
with automatic retraction

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems.

Pipe pressing joints	Ø 10–108 (110) mm Ø ¾–4"
----------------------	-----------------------------

Complete range of REMS pressing tongs/  
pressing rings for all common pressfitting systems,  
see page 182–212.

**REMS Power-Press ACC – universal up to Ø 110 mm.  
With automatic circuit control. Secure crimping  
in seconds. Automatic locking of pressing tongs.**

**System advantage**  
Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked by a \* have another connection (**Patent EP 1 223 008, Patent US 6,739,172**) and also fit the manual radial press REMS Eco-Press.  
Thus simple, inexpensive stocking.

**Pressing tongs/pressing rings  
for all common systems**  
Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 182–212). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 212.

**Design**  
Compact, robust, job site-proven. Small in size, slender design, drive unit only 4.7 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings.

**Pressing operation by touch-control with ACC**  
For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

**Drive**  
Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.



Tested by electrosuisse >>>  
German Quality Product



Supply format		
<b>REMS Power-Press ACC Basic-Pack.</b> Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints Ø 10–108 (110) mm, Ø ¾–4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50–60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.		
Version	Art.-No.	
In sturdy steel case.	577010	
In L-Boxx system case.	577013	
Other voltages on request.		



Accessories		
Description	Art.-No.	
<b>REMS Power-Press ACC Drive Unit</b>	577000	
<b>REMS pressing tongs/pressing rings</b> see page 182–212.		
<b>REMS cropping tongs</b> for threaded rods see page 215.		
<b>REMS cable shear</b> for electric cable see page 215.		
Steel case with insert	570280	
L-Boxx system case with inserts	571283	

